

PROFI MOTO 13 + 2 METERS, H05VV-F 2x1.0

GENERAL CARD



TECHNICAL PARAMETERS

Cat. number:	305504
Ingress protection:	IP20
Supply voltage [V]:	230V/50Hz
Thermal protection:	YES
Rotatable:	YES
Total cable length:	13 + 2 meters
Cable type:	H05VV-F 2x1.0
Maximum load for coiled extension cord:	920W (4A)
Maximum load for Extended extension cord:	2300W (10A)

CHARACTERISTICS

Automatic reel extension cord designed for use in car workshops and industry. The automatic reel is screwed to the wall or ceiling and connected to the power supply. The spool has a cable length management system that locks the cable at a predetermined length so we have easy access to the desired place. The product is intended for wall and ceiling mounting with the possibility of horizontal and vertical operation. The extension reel can be rotated up to 180 degrees. Solid plastic housing. Built-in thermal switch. The automatic winding reel is intended for indoor use only and in a dry environment.

APPLICATION

Car workshops, car and truck services, industry.

PROFI MOTO 13 + 2 METERS, H05VV-F 2x1.0

GENERAL CARD

TECHNICAL PARAMETERS TABLE

Index:	305504	Colour of the body:	blue
Thermal protection:	YES	Cable - length [m]:	13 + 2
Lock of the cable:	YES	Dimensions (H/W/T/S) [mm]:	370/135/280
Supply voltage [V]:	220-240	Category / type:	extension cords
Electrical protection class:	II	Warranty [years]:	2
Maximum load for coiled extension cord:	920W (4A)	Working environment temp [°C]:	from -20 up to +35
Maximum load for extended extension cord:	2300W (10A)	Cable - type:	H05VV-F 2x1.0
Thermal protection:	YES	Manual:	YES
Ingress protection:	IP20		
Plug:	UNI-SCHUKO		

Card creation date: 26 June 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10 proc..



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 81/2023