



Lighting
Light Promo

2024 / 2025

■ Standard



Taurus MultiBattery

IP65 IK08

- Luminous flux: max 5000 lm
- Body made of impact-resistance plastic material
- Comes with 2 switches and 4-step adjustment of:
 - » luminous flux
 - » colour temperature
- Battery discharge indicator
- Adjustable bracket – up to 150 degrees
- Estimated battery-operated runtime for a 5 Ah battery:
 - » 500 lm, working time: 20 h
 - » 1500 lm, working time: 7 h 15 min
 - » 2500 lm, working time: 4 h 30 min
 - » 5000 lm, working time: 2 h 15 min
- Adjustable light colour temperature: 2700K, 3500K, 4500K, 5500K, 6500K
- 5-step indicator showing battery charge level
- Dimensions of the luminaire: 280 x 280 x 148 mm



Battery adapters:

- Bosch Professional 18V
- Milwaukee 18V
- DeWALT 18V
- Makita 18V
- Metabo 18V

256882 Taurus MultiBattery LED
EAN: 5905963256882 99 EUR

Handy Future LED



Lightweight and compact LED workplace lamp

- Light source: 3 W COB LED + 3 W LED
- Luminous flux: 60 and 150 lm
- Strong magnetic fastener in the base
- Robust body
- 2 lighting modes
- Ingress protection class: IP20
- Swivel hook
- Charging time: 3.5 h
- Lighting time: 2.5 h
- Battery charge indicator
- The set includes a Type C charging cable
- Dimensions: 155x40x20 mm

608551 Handy Future LED
EAN: 5905963608551 14 EUR

Handy Multi LED



Lamp with POWER BANK function

- Light source: 5 W COB LED + 2x3 W LED
- Luminous flux: 240 and 400 lm
- Strong magnetic fastener in the base
- Robust body
- Battery charge indicator
- Ingress protection class: IP40
- Charging time: 3.5 h
- Lighting time: 2.5 – 4 h
- Smooth dimming and brightening
- POWER BANK function – enables to recharge other battery devices
- The set includes a Type C charging cable
- Dimensions: 150x48x39 mm

608568 Handy Multi LED
EAN: 5905963608568 24,50 EUR

Handy Slim LED



Slim version for hard-to-reach places

- Light source: COB LED
- Luminous flux up to 360 lm
- Strong magnetic fastener in the base
- Protection class III
- Swivel hook
- 3.7 V 2000 mAh Li-Ion battery
- Lamp covered with rubber
- 4.5 hours of battery life
- Battery charge indicator
- Smooth dimming and brightening
- The set includes a Type C charging cable
- Dimensions: 150x36x31 mm

608698 Handy Slim LED
EAN: 5905963608698 19,50 EUR

Head Multi LED



A headlamp that allows for detaching the lighting unit from the headband and using it as an independent torch.

- luminous flux: max. 500 lm
- Light source: COB LED
- 1 m USB-C charging cable included
- Dimensions: 99/50/61 mm
- Weight: 120 kg
- 3.7 V 1500 mAh Li-Ion battery
- Lamp equipped with a motion sensor
- Non-slip strip
- Charging time: 4.5 h
- Working time (battery): 6 h

334498 Head Multi LED
EAN: 5905963334498 29,80 EUR

Optim LED



A classic in its genre

- Light source: SMD LED
- Luminous flux: 230 lm
- Power: 2 W
- Ingress protection class: IP20
- Protection class: II
- Cover made of PVC
- Lid and handle made of PP
- Swivel hanger
- Weight: 400 g
- Cord: 5 m H05W-F 2x0,75 m²

205958	Optim LED EAN: 5905963205958	12,50 EUR
--------	---------------------------------	-----------

Magnum Standard 32 W



- Ingress protection class: IP54
- Impact resistance: IK10
- Rated power: 32 W
- Colour temperature: 4000 K
- Luminous flux [lm]: 3600 lm
- Nominal supply voltage: 220-240 V
- Rubber cable H07RN-F 3x1.5mm² (3m)
- One socket for connecting other electrical devices or connecting luminaires in series

406416	Magnum Standard 32 W (french standard) EAN: 5905963406416	54 EUR
406423	Magnum Standard 32 W (SCHUKO standard) EAN: 5905963406423	54 EUR

Magnum Standard 50 / 78 W



- Ingress protection class: IP54
- Impact resistance: IK10
- Rated power: 50 / 78 W
- Colour temperature: 4000 K
- Luminous flux [lm]: 5500 / 9500 lm
- Nominal supply voltage: 220-240 V
- Rubber cable H07RN-F 3x1.5mm² (3m)
- One socket for connecting other electrical devices or connecting luminaires in series

406478	Magnum Standard 50W (french standard) EAN: 5905963406478	79 EUR
406485	Magnum Standard 50W (SCHUKO standard) EAN: 5905963406485	79 EUR
406546	Magnum Standard 78 W (french standard) EAN: 5905963406546	98 EUR
406522	Magnum Standard 78 W (SCHUKO standard) EAN: 5905963406522	98 EUR

Magnum Standard 20 W XS Basic



- Ingress protection class: IP54
- Impact resistance: IK10
- Nominal power: 20 W
- Colour temperature: 4000 K
- Luminous flux [lm]: 1600 lm
- Nominal supply voltage: 220-240 V
- H07RN-F 2x1 mm² (3 m) rubber cable
- Diffuser material: PC
- Illumination angle: 120°
- Net weight: 1 kg

256943	Magnum Standard 20 W XS Basic EAN: 5905963256943	29 EUR
--------	---	--------



3 m steel stand



Professional steel stand for heavy loads

- Height when extended: 3 m, folded: 1,2 m
- Height Leg spacing: 1,34 m
- Pipe diameter (legs): 2, 5 cm
- Load capacity: 30 kg
- Weight: 5,4 kg
- Colour: black
- Available version with mounts to attach the stand to the ground

000294	3 m steel stand – for Giant LED luminaire EAN: 5905963000294	74 EUR
250385	3 m steel stand with securing mounts – for Giant LED luminaire EAN: 5905963250385	78 EUR
000300	Crossbar for mounting the Giant luminaire on a stand EAN: 5905963000300	29,50 EUR
000812	CLICK HEAD system enabling quick installation of the luminaires EAN: 5905963000812	14,90 EUR

4,3 m steel stand



- Height when extended: 4,3 m
- Height when folded: 140 cm
- Pipe diameter (top): 3,5 cm
- Load capacity: 50 kg
- Weight: 22,5 kg
- Colour: black
- Designed for: Magnum LED and Illuminator LED luminaires

608773	4.3 m steel stand EAN: 5905963608773	249 EUR
--------	---	---------

Future Stand



Professional stand with a quick-mount head for luminaires

- Future Stand with Click Head system
- Stand enabling tool-free and quick assembly of all luminaires from the Magnum Future family
- Height when extended: 2 m or 3 m
- Height when folded: 108 cm
- Leg spacing: 92 cm
- Pipe diameter (legs): 3,5 cm
- Load capacity: 16 kg
- Colour: black
- Accessories available:
 - CLICK HEAD system enabling quick installation of the luminaires

000737	Future Stand – 2 m EAN: 5905963000737	59,50 EUR
000812	CLICK HEAD system enabling quick installation of the luminaires EAN: 5905963000812	14,90 EUR
608766	Future Stand – 3 m EAN: 5905963608766	69,50 EUR

IP44 drum extension cords

IP44 drum extension cords are specialised extension cords intended for use on construction sites or in workshops. The rubber cable is wound on a drum to facilitate its coiling and transportation. The high ingress protection (IP44) also allows it to be used outdoors in different weather conditions.

Our extension cords are characterised by the following features:

- Regardless of the cable's length, they allow for quick unwinding and coiling
- Thanks to their well-thought-out design, drum extension cords are easy to use and significantly improve working comfort.
- The extension cord is suitable for use in workshops, on construction sites, for household purposes, and for garden works
- The extension cord features a built-in thermal switch to prevent overheating
- The IP44 outlets with are equipped with covers, allowing for outdoor use in different weather conditions
- The drum features a cable handle and a brake mechanism to prevent accidental and excessive unwinding of the extension cord
- It is perfect for connecting various electrical devices such as power tools, lawnmowers, vacuum cleaners, construction equipment, and many more
- It is made of a flexible cable that facilitates coiling



612381	IP44 25 m H07RN-F 3G 1.5 mm ² (french standard) EAN: 5905963612381	59,00 EUR
612343	IP44 25 m H07RN-F 3G 1.5 mm ² (SCHUKO standard) EAN: 5905963612343	59,00 EUR
612398	IP44 40 m H07RN-F 3G 1.5 mm ² (french standard) EAN: 5905963612398	79,00 EUR
612350	IP44 40 m H07RN-F 3G 1.5 mm ² (SCHUKO standard) EAN: 5905963612350	79,00 EUR
612404	IP44 25 m H07RN-F 3G 2.5 mm ² (french standard) EAN: 5905963612404	79,00 EUR
612367	IP44 25 m H07RN-F 3G 2.5 mm ² (SCHUKO standard) EAN: 5905963612367	79,00 EUR
612411	IP44 40 m H07RN-F 3G 2.5 mm ² (french standard) EAN: 5905963612411	104,00 EUR
612374	IP44 40 m H07RN-F 3G 2.5 mm ² (SCHUKO standard) EAN: 5905963612374	104,00 EUR



Distribution board with handle



- Polyamide housing with very high impact resistance
- Handle for easy transport
- Sturdy metal foot
- The housing is equipped with CEE 2x16 A 400 V (5-pin) sockets, 4x230 V
- Anti-twist system – cable with high resistance to twisting
- Socket with self-closing flap for enhanced safety

031939	1.5 m H07RN-F 5x 2.5 mm 2x16 A, 4x230 V distribution board (S), PL-FR grounding EAN: 5905963031939	79 EUR
--------	---	--------



The suggested prices do not include VAT

The promotional campaign lasts while stocks last!

From the moment the above promotional leaflet comes into force, all current promotional campaigns shall expire. Sale carried out through specialised points only. We reserve the right to correct errors and change technical descriptions of products during the promotion. Prices valid until the end of September 2025.



Lena Lighting

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 (61) 28 60 300, e-mail: omp@lenalighting.pl

www.lenalighting.com

Distributor: